



# HDS 7/10-4 M

Medium class hot water pressure washer with a host of user-friendly features.












### 1 Efficiency

- In the Eco setting the unit operates in the most economical temperature range (60°C) with full water flow.
- Burner cycles are optimised to reduce fuel consumption by up to 20% compared to full-load operation.

### 2 Maximum efficiency

- Highly efficient burner technology.
- 4-pole, slow-running electric motor guarantees a long working time.



#### 3 Operational reliability

- The large, integrated fine-mesh water filter reliably protects the high-pressure pump against dirt particles.
- An integrated exhaust gas thermostat switches off the drive motor if the exhaust gas temperature exceeds 300°C.

#### 4 Storage

- Safe and ample storage for protective gear, accessories and cleaning agents.
- Storage hooks for power cord and high-pressure hose.

# **TECHNICAL DATA AND EQUIPMENT.**

### KARCHER



#### HDS 7/10-4 M

- Axial pump with turbo blowerEconomical ecolefficiency mode
- SDS system

Technical data		
Order Number		1.077-901.0
EAN code		4054278140032
Current type	Ph / V / Hz	1 / 240 / 50
Flow rate	l/h	350-700
Pressure	bar / MPa	30-100 / 3-10
Max. temperature	°C	80 / 155
Power rating	kW	3,4
Consumption fuel oil	kg/h	4,6
Fuel tank	1	25
Weight	kg	159,3
Dimensions (L x W x H)	mm	1330 × 750 × 1060

#### Equipment

		20 + 10 l tank	Electronic service control with LED display	•
Trigger gun		EASY!Force Advanced	Two detergent tanks	
High-pressure hose	m	10 / Longlife	Dry running protection	
Spray lance	mm	1050		
Power nozzle				
Servo Control		•		
ANTI!Twist		•		
Anti-twist system (AVS)		-		
Tanks for detergent, scale inhibitor an fuel can be filled from outside	ıd	•		
Control panel with indicator lamps				
Pressure switch control				
Included in delivery.				

## KARCHER







				1			
				Max. working			
		Order Number	ID	pressure	Length	Price	Description
Standard with unions on both sides							
High-pressure hose, 10 m DN 8, AVS trigger gun connector	1	6.110-031.0	ID 8	315 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu- al coupling. Further data: DN 8/155°C/315 bar.
High-pressure hose, 15 m DN 8, AVS trigger gun connector	2	6.110-030.0	ID 8	315 bar	15 m		15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu- al coupling. Further data: DN 8/155°C/315 bar.
High-pressure hose, 20 m DN 8, AVS trigger gun connector	3	6.110-032.0	ID 8	315 bar	20 m		20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu- al coupling. Further data: DN 8/155°C/315 bar.
High-pressure hose, 30 m DN 8, including rotary coupling	4	6.110-014.0	ID 8	315 bar	30 m		With rotary coupling, 2 x M 22 x 1.5
High-pressure hose, 15 m DN 10, 220 bar, extension	5	6.110-042.0	ID 10	220 bar	15 m		15 m high-pressure hose M 22 x 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.
High-pressure hose, 20 m DN 10, 220 bar, extension	6	6.110-043.0	ID 10	220 bar	20 m		with union on both sides, M 22 x 1.5 with anti-kink protec- tion. NW 10/155°C/220 bar
High-pressure hose, 25 m DN 10, extension, not rotatable	7	6.110-044.0	ID 10	220 bar	25 m		
Hose assembly premium DN10 22MPa 40m	8	6.110-045.0	ID 10	220 bar	40 m		
Hose assembly premium DN12 21MPa 15m	9	6.110-059.0	ID 12	210 bar	15 m		High-pressure hose for water volumes greater than 1,800 l / h. With union on both sides. 2x M 22 x 1.5 with anti-kink
Hose assembly premium DN12 21MPa 40m	10	6.110-060.0	ID 12	210 bar	40 m		protection.
Hose assembly TR DN10 22MPa 10m	11	6.110-041.0	ID 10	220 bar	10 m		
Longlife 400 with unions on both si							
High-pressure hose Longlife 400, 30 m DN 8, including rotary coup- ling	12	6.110-023.0	ID 8	400 bar	30 m		With rotary coupling, 2 x M 22 x 1.5
High-pressure hose Longlife 400, 20 m, DN 8, extension	13	6.110-027.0	ID 8	400 bar	20 m		with rotary coupling, 2 x M 22 x 1.5
High-pressure hose Longlife 400, 15 m, DN 8, including rotary coup- ling	14	6.110-029.0	ID 8	400 bar	15 m		With rotary coupling, 2 x M 22 x 1.5
High-pressure hose packaged	15	6.110-038.0	ID 8	400 bar	10 m		Durable, 10 m long high-pressure hose (ID 8) with double steel reinforcement and EASY!Lock hand screw connection at both ends and ANTI!Twist. Approved for 400 bar pressu- re.
High-pressure hose 1.5 m, DN 8, including connectors	16	6.110-024.0	ID 8	400 bar	1,5 m		1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink pro- tection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).
Food industry version with unions	on bot	h sides					
High-pressure hose, 10 m ID 8, suitable for food industry, extensi- on piece		6.110-051.0	ID 8	250 bar	10 m		10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.
High-pressure hose, 20 m ID 8, suitable for food industry, extensi- on piece	18	6.110-052.0	ID 8	250 bar	20 m		20 m high-pressure hose (DN 8) with swivel coupling. Non- discolouring outer layer for use in the food industry. Con- nectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.



		Order Number	ID	Max. working pressure	Length	Price	Description
Longlife food industry version with	unior	s on both sides					
High pressure hose food DN 8 / 10 m	19	6.110-053.0	ID 8	400 bar	10 m		Longlife HP hose for use in the food industry. Außende- cke## animal-grease-resistant, non-colour-bleeding materi- al. With rotary coupling, 2 x M 22 x 1,5

Included in delivery.  $\Box$  Available accessories.  $\blacktriangle$  Extension hose.

## KARCHER




		Order Number	Flow rate			Price	Description
Trigger guns			1	1	1		
EASY!Force Advanced	1	4.118-005.0					Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.
Conversion kit 1 from high pressu- re hose	2	4.111-050.0					A conversion kit which enables secure connection from an M22 hose onto our innovative EASY!Force trigger gun. The kit includes the EASY!Force Trigger gun, adaptors and lance.
Conversion kit 2 from device	3	4.111-051.0					Provides all the parts required to utilise our EASY!Force technology even on our non-Easy!Force machines. Including [ adaptors, lance, Easy!Force trigger gun and hose.
Conversion kit 3 only EASY!Force	4	4.111-052.0					A conversion kit for the EASY!Force gun, which includes the correct adaptors to conncect to the M22 style lance and hose.
Servo Control							
Servo control	5	4.118-008.0	750-1100 l/h				Water quantity and pressure regulated directly from the hand spray gun.
Quick connect							
Quick-fitting pipe union coupler trapezo	6	2.115-000.0					For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray [ lance interface. With M 22 x 1.5 internal thread.
Quick-fitting pipe union plug nipp- le tra	7	2.115-001.0					Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22 x 1.5 external thread. [

	Z				-	5		
		Order Number	Max. working pressure	Length		Price	Description	
Rotating spray lances			1	1				
1050 mm lance, rotatable, ergono- mic	1	4.112-000.0	300 bar	1050 mm			1050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360°	
Nozzle Light	2	2.680-002.0		125 mm			under pressure. LED work light for assembly on EASY!Force spray lances, providing a clear view in poor lighting conditions ensuring controlled cleaning results.	
Lance 250 mm, non-rotatable	3	4.112-027.0	300 bar	250 mm			600 mm stainless steel lance (manual coupling) with ergono-	
550 mm lance, non-rotatable Rotatable lance, 600 mm, ergono-	4	4.112-024.0 4.112-007.0	300 bar 300 bar	400 mm 600 mm			under pressure.	
mic	5	4.112-007.0	500 Dai	000 11111			· · · · · · · · · · · · · · · · · · ·	
Lance 850 mm, rotatable, ergono- mic	6	4.112-006.0	300 bar	840 mm			850 mm stainless steel lance (manual coupling) with ergono- mic handle for ease of use and protection. Rotatable 360° under pressure.	
Lance 1550 mm, rotatable, ergo- nomic	7	4.112-018.0	300 bar	1550 mm			1550 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.	
Lance 2050 mm, rotatable, ergo- nomic	8	4.112-021.0	300 bar	2050 mm			2050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360°	
Jet pipe extension TR 1000 mm	9	4.112-048.0	300 bar	1000 mm			under pressure. Spray lance extension with EASY!Lock connection. Length	П
Double lance							1000 mm.	
Double lance 960 mm	10	2.112-016.0	310 bar	960 mm			960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use ( e.g. stable cleaning).	
Angular spray lance WC and gutter lance	11	4.112-029.0					Stainless steel lance WC and gutter with nozzle insert. Spe- cially shaped for effective and hygienic cleaning of gutters	
							and toilets.	_
Flexible spray lance Flexible lance 1050 mm	12	4.112-035.0	210 bar	1050 mm			1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	
Articulated joint TR 20	13	4.112-057.0	300 bar				For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer.	
Telescopic spray lance								
Telescopic jet pipe	14	4.112-037.0	225 bar	5400 mm			Can be continuously extended from 1.8 to 5.4 m. For cleaning areas that are difficult to reach, such as ceilings or facades. With integrated HD trigger gun, M 22 x 1.5 connec- tion with rotary coupling. Connection for M 18 x 1.5 nozzles.	
Restraint belt for telescopic jet pipe	15	6.373-987.0					Convenient strap for relief when working with the telesco- pic spray lance (6.394-690). The burden is optimally distri- buted on the body and longer periods of use are possible.	
Gutter cleaner								
Gutter cleaning lance	16	2.112-015.0		960 mm			The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	
Undercarriage spray lance		4 112 022 0		700 mm			Chainless shall lange for effective and every sector by the sector	
Underbody lance	17	4.112-032.0		700 mm			Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	

■ Included in delivery. □ Available accessories. ▲ Extension hose.





		Order Number	Max. working pressure	Length		Price	Description	
Additional handle								
Additional handle for EASY!Lock spray lances	18	4.321-380.0					Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task.	
Weed control								
WR 50	19	2.114-013.0					In combination with a hot water high-pressure cleaner from Kärcher, the 50 cm wide weed remover WR 50 is ideal for removing weeds. It comes with an adaptive chassis and nozzle adapter.	
WR 20	20	2.114-014.0					For thorough weed removal: The WR 20 weed remover for use with a hot water high-pressure cleaner from Kårcher. Equipped with a 20 cm wide nozzle bar and nozzle adapter.	
WR 100	21	2.114-015.0					For thorough weed removal: The WR 100 weed remover for use with a hot water high-pressure cleaner from Kårcher. Equipped with a 100 cm wide nozzle bar and nozzle adap- ter.	
WR 10	22	2.114-016.0					In combination with hot water high-pressure cleaners our WR 10 weed remover enables fast and thorough weed removal. With 10 cm spray head and nozzle adapter.	



	Order Number	Nozzle size				Price	Description
1	2.113-011.0	54					Flat jet nozzle for large area performance and stubborn dirt.
2	2.113-035.0	55					High-pressure nozzle with powerful jet for extremely stub- born dirt.
3	2.113-047.0	55					Fan jet nozzle with 15° spray angle suitable for stubborn dirt.
							·
4	2.113-055.0	55					Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.
	2 3 4		2     2.113-035.0     55       3     2.113-047.0     55       4     2.113-055.0     55	1     2.113-011.0     54       2     2.113-035.0     55       3     2.113-047.0     55       4     2.113-055.0     55	1     2.113-011.0     54       2     2.113-035.0     55       3     2.113-047.0     55       4     2.113-055.0     55	1     2.113-011.0     54       2     2.113-035.0     55       3     2.113-047.0     55       4     2.113-055.0     55	1     2.113-011.0     54       2     2.113-035.0     55       3     2.113-047.0     55       4     2.113-055.0     55

 $\blacksquare$  Included in delivery.  $\Box$  Available accessories.  $\blacktriangle$  Extension hose.



		Order Number	Max. working pressure	Nozzle size		Price	Description
Dirt blaster, large							·
Dirt blaster - without changeover function	1	4.114-036.0	300 bar	55			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.
Angle vario nozzle 0°-90°							
Variable angle nozzle 0-90°	2	4.113-006.0		80			Variable angle nozzle for spray angle adjustment from 0° to $90^\circ$ . For easy adjustment to all kinds of soiling and surfaces.
■ Included in delivery. □ Av	ailable	e accessories.	▲ Extension ho	ose.			

HDS 7/10-4 M, 1.077-901.0, 2019-12-04

### KARCHER

				4	5-6	$ \begin{array}{c} \begin{array}{c} \begin{array}{c} \end{array}\\ \end{array}\\ \end{array}\\ \end{array} $	
		Order Number			Price	Description	
Nozzle union							
Nozzle screws	1	4.112-011.0				Nozzle screws with protectors for high-pressure and power	
HP detergent injector						nozzles	1
Detergent injector for high and	2	4.637-032.0				Detergent injector for independent high and low pressure	
low pressure (without nozzles)	_				 	dosage. Maximum dosage about 15%.	
Detergent injector for high pressu-	3	4.637-033.0				Cleaning agent dosage at high pressure 3 - 5 %	
re Machine-specific nozzle kit with ord	lor no	3 637-170					_
Nozzle insert trapezoidal thread	4	4.769-011.0				For HD/HDS 750 - 1000 l/h. Consists of nozzle insert + HP	
HDS-GER						power nozzle + union	
Nozzle insert with order no. 3.637-0							
Nozzle insert for Order No. 3.637- 001, high-pressure for machines up to 1100 l/h.	5	4.769-003.0				Nozzle insert for detergent injector 3.637-001 for high- pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Low pressure for units rated up to	6	4.769-001.0				For low pressure with machines up to 1.100 l/h	
1100 l/h							Ľ
Rotary coupling Rotary coupling	7	4.111-021.0				Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.	
Coupling		I	I			n. whith ship protection.	
Coupler -2xM22x1,5	8	4.111-037.0				Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m.	
Connector Nozzle connector/screw connector	9	4.111-022.0				Nozzle connector/screw connector for connecting high- pressure nozzles and accessories to the high-pressure trig- ger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.	
Y distributor	10	4.111-024.0				Offers the option to connect two spray units to the machine.	· _
Short spray unit	11	4.111-038.0				Installation on the high pressure outlet. For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). Not compatible with	
						triple nozzles.	
Adapter EASY!Lock	10	4 111 020 0				Adaptor 1 to connect the old been with the service	
Adapter 1 M22AG-TR22AG Adapter 2 M22IG-TR22AG	12 13	4.111-029.0 4.111-030.0				Adapter 1 to connect the old hose with the new hose Adapter 2 to connect the old device with the new hose and	
Αυαριεί z ΙνίζζΙΟ-ΤΚΖΖΑΟ	13	4.111-030.0				the old gun with the new hose	
Adapter 3 M22IG-TR22AG	14	4.111-031.0				Adapter 3 to connect the old gun with the new spray lance	
Adaptor M22 Curing	4.5	4 111 022 0				and new servo regulator	$\downarrow$
Adapter M22 - Swivel	15	4.111-032.0				M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connec- tion.	
Adapter 5 TR22IG-M22AG	16	4.111-033.0				Adapter 5 to connect the new gun with the old spray lance	
Adapter 6 TR22IG-M22AG	17	4.111-034.0				and new servo regulator with the old spray lance Adapter 6 to connect the new device with the old hose and	_
	4.0	4 4 4 4 4 0 2 5 0				the old hose with the new gun	$\downarrow$
Adapter 7 M18IG-TR20AG	18	4.111-035.0				Adapter 7 to connect the old spray lance with the new nozzle	
Adapter 8 TR20IG-M18AG	19	4.111-036.0				Adapter 8 to connect the new spray lance with the old	
■ Included in delivery. □ Ava			Extension hos			nozzle	1



		Order Number		Price	Description	
ADAPTER for replacement TR22IG- M22AG Er	20	4.111-046.0			Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	
Flue pipe						
Flue gas adapter	21	4.656-149.0			Flue gas adapter with draught damper for flue pipe connec-	
	22	4.656-080.0			tion (adapter for HDS burners for connection to a stack system).	Γ

ן ר

ר ר

٦ [

### KARCHER

] ר

		5		6-7		8-9	
12 13		14		15	Ľ	16	
		Order Number	Max. working pressure	Nozzle size	Diame- ter	Price	Description
Pipe cleaning hose, ID 6 Hose assembly TR pipe cleaning DN6 max.2	1	6.110-046.0	250 bar				The 10 m pipe cleaning hose is a highly flexible high pressu- re hose for pipe interior cleaning (threaded connection for nozzle R 1/8).
Pipe cleaning hose, DN 6, 20 m, 220 bar	2	6.110-008.0	250 bar				20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle).
Hose assembly TR pipe cleaning DN6 max.2	3	6.110-047.0	250 bar				The 30 m pipe cleaning hose is a highly flexible high pressu- re hose for pipe interior cleaning (threaded connection for nozzle R 1/8).
Pipe cleaning nozzle		1	1		1 1		
Dirt blaster pipe cleaning D21/060 Dirt blaster pipe cleaning D30/060	-			60 60	21 mm 30 mm		The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient hand- ling.
Nozzle pipe cleaning size 80	6	5.763-087.0		80	24 mm		Pipe cleaning nozzle with 24 mm diameter. With 4 nozzles [
Nozzle pipe cleaning size 120	7	5.763-089.0		120	24 mm		Pipe cleaning nozzle with 24 mm diameter. With 8 nozzles [
Pipe cleaning nozzle	8	5.763-015.0		55	16 mm		16 mm pipe cleaning nozzle with internal thread. Various jet [
	9	5.763-016.0		60	16 mm		directions for environmentally-friendly cleaning of blocked drains and pipes.
	10	5.763-021.0		70	30 mm		30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.
Rotating pipe cleaning nozzle	11	6.415-428.0		50	16 mm		Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blo- cked drains and pipes.
Barrel and tank cleaning							· · · · · · · · · · · · · · · · · · ·
Barrel cleaner BC 14/12	12	2.112-020.0					The barrel cleaner BC 14/12 is a spray unit for the internal cleaning of containers and drums - in particular oak barrels [ with a capacity between 225 and 600 liters.
HKF 50 spray head, brass							
HKF 50 spray head, brass		3.631-058.0					Interior cleaning head for barrels and containers with bung- holes of 50 mm and more.
Nozzle kit for HKF 50 spray head (3		1	9.0)		1 1		
Nozzle 090 for single nozzle ope- ration HKF 50	14	6.415-447.0		90			Nozzle for single-nozzle operation [

ר ר

7 [

Double handle. Precise control of the spray head

Screw plug for using a spray head with one nozzle

16 with one nozzle ■ Included in delivery. □ Available accessories. ▲ Extension hose.

15

ration HKF 50

the spray head

Double handle for exact control of


Screw plug for using a spray head

2.863-036.0

5.411-061.0

HDS 7/10-4 M, 1.077-901.0, 2019-12-04

## KARCHER



▲ Extension hose.

## KARCHER



□ Available accessories.

## KARCHER



■ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 7/10-4 M, 1.077-901.0, 2019-12-04



		Order Number	Nozzle size		Price	Description
Wet blasting attachment (without n	nozzle)					·
Wet blasting attachment with flow control (without nozzles)	1	4.115-000.0				Paint, rust and scale removal made easy: Kärcher wet blas- ting attachment with flow control for adding blasting abrasi- ve to the high-pressure jet.
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0				Paint, rust and scale removal made easy: Kärcher wet blas- ting attachment with flow control for adding blasting abrasi- ve to the high-pressure jet. Without flow control.
Nozzle pack for wet blasting attach	ment					
Nozzle pack TR wet jet set 0050	3	2.112-023.0	50			Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment
Boron carbide nozzle						•
Boron carbide nozzle, for machi- nes as of 1000 l/h	4	6.415-084.0	6 mm			In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.

 $\blacksquare$  Included in delivery.  $\hfill\square$  Available accessories.  $\hfill\blacksquare$  Extension hose.

## KARCHER



		O de New I			Builden		
		Order Number			Price	Description	
Crane lifting kit							
Crane loading kit for HDS middle and super class	1	2.642-424.0				Effortless loading by crane.	
Transport eyelet attachment kit	2	2.644-053.0				Robust transport eyelet attachment kit for the secure fixing of HDS Medium and Super Class pressure washers during transport.	
Flame monitoring attachment kit							
ABS flame monitor for HDS M/S	3	2.641-796.0				More safety thanks to ABS HDS M/S flame monitoring sys- tem: A light sensor monitors the burner flame. The fuel supply cuts out automatically if the flame extinguishes.	
Accumulator kits							
Add-on accumulator for HDS M/S	4	2.641-803.0				The accumulator can be mounted on the HDS machine in order to dampen pressure surges, which conserves the machine's line system.	
Remote control set							
Remote control set	5	2.642-157.0				Remote control for the machines of the HDS Middle and Super class with the functions on/off, hot/cold water and cleaning agent on/off. For mounting to a wall.	
Coin-op remote control							
Coin-op remote control	6	2.642-158.0				Retrofittable coin acceptor for machines in the HDS Middle and Super class for self-service operation. For installation on the machine.	



		1		1				
							De-	
		Order Number	Quantity			Price	scripti- on	
a		order Homber	Quantity			FILE		
Geka coupling		1		1	1			I.
With hose nozzle, R 3/4"	1	6.388-455.0					with hose liner	
With hose nozzle, R 1"	2	6.388-465.0					with	-
With Hose Hozzle, K 1	2	0.300 403.0					hose barb	
Hose coupling	3	6.388-458.0					with	
							female	
							thread	
Suction filter								
Water filter	4	6.414-956.0					Suitable for ponds,	
							storage	
							tanks or	
							similar,	
							polyami	
							de filter	
							casing,	
							stainless	
							steel strainer.	
							800 µm	
							mesh, R	
							3/4" and	
							R 1"	
							connec-	
							tion,	
							without	
							non-	
							return	
Suction filter with check valve		4.730-012.0					valve Brass	
SUCTION THEF WITH CHECK AGIAG	5	4.730-012.0					suction	
							filter	
							suitable	
							for	
							ponds,	
							storage	
							tanks,	
							etc. With	
							check	
							valve.	<u> </u>



	Order Number	Quantity		Price	De- scripti- on	
Fine-mesh water filter						







		Order Number	Flow rate		Price	Description	
Push-on washing brush						1	
Push-on wash brush, M 18 x 1.5	1	4.113-001.0				Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.	
Rotating washing brush							
Rotating wash brush for < 800 l/h machines, nylon bristles	2	4.113-004.0	500-800 l/h			The rotating wash brush gently removes fine dust and traf- fic film from all surfaces. Temperature resistant up to $60^{\circ}$ C. (M 18 x 1.5, replaceable brush insert).	
Rotating wash brush for < 800 l/h machines, natural bristles	3	4.113-003.0	500-800 l/h			Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60°C, M 18 x 1.5 (replaceable brush insert).	