

NT 65/2 Ap

Powerful, twin-motor wet & dry vacuum for professional applications. Featuring the Ap semi-automatic filter clean system for constantly high suction power.

1 On-board practical storage

- Large on-board storage area for tool and accessory storage.

2 Integrated drain hose (oil-resistant)

- Easily accessible drain hose for convenient liquid disposal.

3 ApClean (semi-automatic filter cleaning system)

- The free filter means that the user can work for long intervals without interruption.
- Optimal suction power with high efficiency.

4 Hose and bend attachment

- Convenient suction hose and bend attachment for easy transport and storage.



NT 65/2 Ap

- Semi-automatic filter cleaning system
- Flat pleated filter (dust class M)
- Drain hose and push handle

Technical data

Order Number		1.667-297.0
EAN code		4039784727342
Current type	Ph / V / Hz	1 / 220 - 240 / 50 - 60
Air flow	l/s	2 x 74
Vacuum	mbar / kPa	254 / 25,4
Container capacity	l	65
Container material		Plastic
Motor rating	W	max. 2760
Standard nominal size		ID 40
Cable length	m	10
Sound level	dB(A)	73
Quantity of motors		2
Weight	kg	20
Dimensions (L x W x H)	mm	567 x 482 x 920

Equipment

Suction hose	m	4	Push handle	■
Suction Tube	piece(s) / m	2 x 0,5 / Metal	Safety class	II
Filter bag		Paper	Caster with brake	■
Wet and dry floor tool	mm	360		
Crevice nozzle		■		
Drain hose (oil-resistant)		■		
Auto shutdown when max. level is reached		■		
Flat pleated filter		Paper		
Bend		■		
Filter cleaning		ApClean (semi-automatic filter cleaning system)		
Sturdy bumper		■		

■ Included in delivery.

NT 65/2 AP

1.667-297.0

KÄRCHER


		Order Number	Quantity	ID	Length	Width	Price	Description	
Flat pleated filter (paper)									
Flat pleated filter	1	6.904-283.0	1 piece(s)					Paper flat pleated filter (BIA-(U,S,G,C) dust class M) suitable for NT 65/2 Eco, NT 65/2 Eco Tc, NT 65/2 Eco Me.	■
Plastic bend									
Elbow packaged NW40 1K	2	2.889-171.0	1 piece(s)	ID 40				Bend for the new clip system in nominal size DN 40.	■
Plastic bend	3	5.031-718.0	1 piece(s)	ID 35				Plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models (except NT Eco M and NT Eco H).	□
	4	5.031-939.0	1 piece(s)	ID 35				Electrically conductive plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models.	□
	5	5.032-427.0	1 piece(s)	ID 40				Electrically conductive plastic bend (DN 40) with C-40 clip system, suitable for all NT vacuum cleaners.	□
Elbow electrically conducting packaged N	6	2.889-148.0	1 piece(s)	ID 35				Ergonomic bend for the new clip system. With airflow control slide, in an antistatic design.	□
All-purpose nozzles (wet/dry)									
Floor tool packaged NW40 360mm	7	2.889-153.0	1 piece(s)	ID 40		360 mm			■
Floor tool DN40-370	8	6.903-018.0	1 piece(s)	ID 40		370 mm		All-purpose aluminium nozzle with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	□
Floor tool neutrally DN40	9	6.906-383.0	1 piece(s)	ID 40		450 mm		All-purpose aluminium nozzle (DN 40) with 450 mm working width. With height-adjustable side rollers, brush strips (6.903-065.0) and oil-resistant squeegees (6.906-146.0). Only for NT vacuum cleaners.	□
Floor tool neutrally DN35	10	6.906-384.0	1 piece(s)	ID 35		370 mm		All-purpose aluminium nozzle (DN 35) with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	□
Wet and dry floor nozzle	11	2.889-117.0	1 piece(s)	ID 40		400 mm		The wet and dry floor nozzle (DN 40) allows quick changing of the squeegees/brush and is ideal for wet vacuum cleaning of large areas.	□
Crevice nozzles									
Crevice nozzle DN 40 300mm 1:50	12	5.130-655.0							■
Crevice nozzle DN35	13	6.900-385.0	1 piece(s)	ID 35	210 mm			Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 210 mm.	□
Crevice nozzle	14	6.900-922.0	1 piece(s)	ID 35	500 mm			Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 370 mm.	□
Crevice nozzle DN40	15	6.905-817.0	1 piece(s)	ID 40	400 mm			Metal crevice tool (DN 40) for vacuuming in crevices and corners. Length: 400 mm.	□
Suction tubes stainless steel									
Set suction tube stainless steel NW40 55	16	2.889-194.0	1 piece(s)	ID 40	550 mm			Stainless steel suction tube set (2 × 0.55 m)	■
Suction tube, ID 40	17	6.902-081.0	1 piece(s)	ID 40	0,5 m			Stainless steel suction tube (DN 40, 0.5 m) only suitable for NT vacuum cleaners.	□
Suction tube	18	6.906-531.0	1 piece(s)	ID 40	1 m			Stainless steel suction tube (DN 40, 1.0 m) only suitable for NT vacuum cleaners.	□
Suction tube, DN 35	19	6.902-154.0	1 piece(s)	ID 35	0,5 m			0.5 m long stainless steel suction tube (ID 35) for wet and dry vacuum cleaners. Ideal for frequent wet vacuuming applications and for vacuuming corrosive components.	□

■ Included in delivery. □ Available accessories.

NT 65/2 AP 1.667-297.0

KÄRCHER



		Order Number	Quantity	ID	Length	Width	Price	Description	
Suction hoses complete (Clip-system)									
Suction hose	20	2.889-138.0	1 piece(s)	ID 40	4 m			4 m suction hose with new bayonet and clip fastener.	■
	21	4.440-678.0	1 piece(s)	ID 40	4 m			4 m electrically non-conductive suction hose with bend, bayonet at vacuum end and C 40 clip connection at accessory end. Without module.	□
Suction hose, complete (clip system), C DN 40, 4 m	22	4.440-679.0	1 piece(s)	ID 40	4 m			4 m electrically non-conductive suction hose with bend (C-DN 40) and module (4.060-474.0), bayonet at vacuum end and C 35 clip connection at accessory end.	□
Suction hose complete (Clip-system), C ID 40, 4 m, el.	23	4.440-728.0	1 piece(s)	ID 40	4 m			With bend and module (4.060-533.0), electrically conductive.	□
Electrically conductive suction hose	24	2.889-137.0	1 piece(s)	ID 35	4 m			4 m suction hose with new bayonet and clip fastener. Electrically conductive.	□
Suction hose	25	2.889-139.0	1 piece(s)	ID 40	2,5 m			Suction hose with new bayonet and clip fastener. Length: 2,5 m.	□
Suction hose, oil-resistant	26	2.889-140.0	1 piece(s)	ID 40	4 m			Oil-resistant suction hose with new bayonet and clip fastener. Length: 4 m.	□
Electrically conductive suction hose	27	2.889-141.0	1 piece(s)	ID 40	4 m			4 m, electrically conductive suction hose with new bayonet and clip fastener.	□
	28	2.889-142.0	1 piece(s)	ID 40	2,5 m			Suction hose, electrically conductive, with new bayonet and clip fastener. 2,5 m long.	□
Flat pleated filter (PES)									
Flat filters (PES)	29	6.904-284.0	1 piece(s)					Flat filter (PES) - BIA-(U,S,G,C) dust class M: rotproof polyester fleece, ideal for wet use and abrasives. Standard for NT 72/2 Eco Tc.	□
Membrane filter / fabric filter									
Membrane filter/fabric filter	30	6.904-282.0	1 piece(s)					Polyester needle fleece membrane/fabric filter - BIA-C -, washable up to 40°C, metal fibres for earthing. Suitable for virtually all industrial two-motor NT vacuum cleaners.	□
HEPA filter for dust class H									
HEPA surface filter	31	6.904-364.0	1 piece(s)					HEPA surface filter - dust class H (H 14) - with glass-fibre layers increases filter capacity when vacuuming health-endangering and carcinogenic dust.	□
Plastic sacks for dust-free disposal									
Plastic sacks for dust-free disposal	32	6.900-698.0	10 piece(s)					PE plastic sack.	□
Special filter bags, wet filter bags									
Special filter bags, wet filter bags	33	6.904-252.0	5 piece(s)					Approved for dust class L, general cleaning, wet and dry, tear-resistant.	□
Bend stainless									
Bend, stainless steel ID 35	34	6.903-141.0	1 piece(s)	ID 35				Stainless steel and crooked, ID 35	□
Bend, stainless steel ID 40	35	6.902-079.0	1 piece(s)	ID 40				Stainless steel and crooked, ID 40	□
Bend metal									
Bend, DN 35, metal	36	6.900-519.0	1 piece(s)	ID 35				Robust, chromium-plated metal bend (DN 35), can be used instead of a plastic bend (with clip system adapter 5.407-112.0; C 35-DN 35, plastic, el.).	□
Bend, DN 40, metal	37	6.900-276.0	1 piece(s)	ID 40				Robust, chromium-plated metal bend (DN 40), can be used instead of a plastic bend (with clip system adapter 5.407-111.0; C 40-DN 40, plastic, el.).	□
Car cleaning nozzles									
Car nozzle	38	6.900-952.0	1 piece(s)	ID 40		90 mm		Angled, flat, plastic car vacuuming tool with about 90 mm working width. Only for NT vacuum cleaners.	□

■ Included in delivery. □ Available accessories.

NT 65/2 AP 1.667-297.0

KÄRCHER



		Order Number	Quantity	ID	Length	Width	Price	Description	
Rubber suction tools, nose 45°									
Rubber suction tools, nose 45°	39	6.902-104.0	1 piece(s)	ID 35	220 mm			45° rubber suction nozzle (DN 35), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	<input type="checkbox"/>
	40	6.902-105.0	1 piece(s)	ID 40	220 mm			45° rubber suction nozzle (DN 40), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	<input type="checkbox"/>
Pipe dusting nozzles									
BRUSH	41	6.903-035.0	1 piece(s)	ID 35				Plastic, pipe diameter 100 mm	<input type="checkbox"/>
	42	6.903-036.0	1 piece(s)	ID 35				Plastic, pipe diameter 200 mm	<input type="checkbox"/>
Suction brushes									
Suction brush DN35	43	6.903-862.0	1 piece(s)	ID 35		70 mm		Rotatable suction brush (DN 35) with natural bristles (cow hair). Bristle size 70x45 mm. Only CV and NT vacuum cleaners.	<input type="checkbox"/>
Suction tubes metal									
Suction tube DN35	44	6.900-514.0	1 piece(s)	ID 35	0,5 m			Chromium-plated metal suction tube (DN 35, 1x0.5 m), standard for virtually all single-motor industrial NT vacuum cleaners.	<input type="checkbox"/>
Repair kits									
Repair set, C 40	45	2.639-873.0	1 piece(s)	ID 40				Repair set (C40) includes threaded hose adapters (without bayonet adapter) for industrial NT vacuum cleaners with clip system.	<input type="checkbox"/>
Repair kit ID 61	46	2.862-038.0	1 piece(s)	ID 61				Suction hose repair kit. Optional for all NT 65/2 and 72/2, NT 993 I, NT 802 I.	<input type="checkbox"/>
Suction hoses (Clip-system)									
Suction hose (clip system), C 40, 10 m	47	6.906-279.0	1 piece(s)	40	10 m			10 m standard suction hose without bend and adapter. With bayonet at vacuum end and C 40 clip connection at accessory end.	<input type="checkbox"/>
Suction hose	48	6.906-321.0	1 piece(s)	40	4 m			4 m suction hose with bayonet and C 40 clip connection. Without bend and adapter.	<input type="checkbox"/>
	49	6.906-714.0	1 piece(s)	40	4 m			With bayonet and clip connection.	<input type="checkbox"/>
	50	6.906-546.0	1 piece(s)	40	4 m			Electrically conductive, 4 m suction hose with bayonet and C 40 clip connection. Without bend and adapter.	<input type="checkbox"/>
Suction hose (Clip-system), C 40, 16 m	51	6.906-635.0	1 piece(s)	40	16 m			With bayonet and clip connection.	<input type="checkbox"/>
Suction hose (clip system), C 40, 10 m, el.	52	6.906-877.0	1 piece(s)	40	10 m			Suction hose with bayonet coupling, electrically conductive.	<input type="checkbox"/>
Suction hoses complete									
Suction hose, complete	53	4.440-264.0	1 piece(s)	ID 61	4 m			4 m standard suction hose with DN 61 bayonet at vacuum end and DN 61 cone at accessory end.	<input type="checkbox"/>
Suction hose, complete, DN 61, 10 m	54	4.440-467.0	1 piece(s)	ID 61	10 m			10 m standard suction hose with DN 61 bayonet at vacuum end and DN 61 cone at accessory end.	<input type="checkbox"/>
Suction hose complete, ID 61, 4 m, oil-resistant	55	4.440-613.0	1 piece(s)	ID 61	4 m			Oil-resistant.	<input type="checkbox"/>
Suction hose complete, ID 61, 4 m, el.	56	4.440-616.0	1 piece(s)	ID 61	4 m			Electrically conductive.	<input type="checkbox"/>
Suction hose, complete	57	4.440-263.0	1 piece(s)	ID 40	4 m			Electrically non-conductive 4.0m standard suction hose with bayonet at vacuum end and DN 40 cone at accessory end.	<input type="checkbox"/>
Suction hose complete, ID 40, 4 m, oil-resistant,	58	4.440-303.0	1 piece(s)	ID 40	4 m			Oil-resistant.	<input type="checkbox"/>
Suction hose, complete	59	4.440-463.0	1 piece(s)	ID 40	10 m			Electrically non-conductive 10.0m standard suction hose with bayonet at vacuum end and DN 40 cone at accessory end.	<input type="checkbox"/>
Suction hose complete	60	4.440-466.0	1 piece(s)	ID 40	10 m			Electrically conductive, 10.0m, ID 40	<input type="checkbox"/>

■ Included in delivery. □ Available accessories.

NT 65/2 AP

1.667-297.0

KÄRCHER



		Order Number	Quantity	ID	Length	Width	Price	Description	
Suction hose complete, ID 40, 10 m, oil-resistant	61	4.440-612.0	1 piece(s)	ID 40	10 m			Oil-resistant.	<input type="checkbox"/>
Connecting sleeves									
Adapter, DN 32/35, with internal thread	62	6.902-077.0	1 piece(s)	ID 32				Electrically non-conductive adapter with internal thread. For connecting two suction hoses without connectors. Suitable for DN 32 or DN 35.	<input type="checkbox"/>
Adapter, DN 40 with internal thread	63	6.900-286.0	1 piece(s)	ID 40				Electrically non-conductive adapter with screw thread at both ends. For connecting 2 DN 40 suction hoses without connectors.	<input type="checkbox"/>
Connecting sleeve, ID 61, with female thread	64	6.902-078.0	1 piece(s)	ID 61				For connecting 2 suction hoses, thread on both sides	<input type="checkbox"/>
Extension hoses (Clip-system)									
Extension hose, C 40	65	6.906-344.0	1 piece(s)	ID 40	2,5 m			2.5 m electrically non-conductive standard extension hose for all C-40 hoses with clip system.	<input type="checkbox"/>
Y-adapter kit									
Y-adapter kit	66	2.637-217.0	1 piece(s)	ID 35				Plastic distributor - suitable for NT vacuum cleaners.	<input type="checkbox"/>
Connecting sleeve C-DN (clip on taper), EL (electroconductive)									
C-ID 35 adapter	67	5.407-112.0	1 piece(s)	ID 35				Connects C 35 hose for ID 35, electrically conductive.	<input type="checkbox"/>
C 40 adapter	68	5.407-109.0	1 piece(s)	ID 40				Electrically conductive adapter (C 40) with DN 35 connection for connecting DN 35 accessories to an industrial C 40 or C-DN 40 suction hose. Suitable for NT vacuum cleaners.	<input type="checkbox"/>
C-DN 40 adapter	69	5.407-111.0	1 piece(s)	ID 40				Connects C 40 hose for ID 40, electrically conductive.	<input type="checkbox"/>
Adapter for electric power tools, clip on, el.									
Sleeve for tool C35EL	70	5.453-042.0	1 piece(s)	ID 35				3-way plastic adapter. For DN 26 to DN 36. For connecting power tools to an industrial C or C-DN 35 suction hose. Suitable for NT vacuum cleaners.	<input type="checkbox"/>
Adapter for electric power tools, C 35, el.	71	5.453-048.0	1 piece(s)	ID 35				Inner Ø 25.4 mm, outer Ø 34.6 mm/ 38 mm, el. Only NT-vacuums.	<input type="checkbox"/>
Connecting sleeve for electric tool C 35, el.	72	5.453-049.0	1 piece(s)	ID 35				Inner Ø 28.6 mm, outer Ø 37.3 mm/ 38.8 mm, el. Only NT-vacuums.	<input type="checkbox"/>
Adapter for electric power tools, C 35, el.	73	5.453-050.0	1 piece(s)	ID 35				Inner Ø 27 mm, outer Ø 36.5 mm/ 38.8 mm, el. Only NT-vacuums.	<input type="checkbox"/>
Connecting sleeve for electric tool C 35, el.	74	5.453-051.0	1 piece(s)	ID 35				Inner Ø 32 mm, outer Ø 39 mm, el. Only NT-vacuums.	<input type="checkbox"/>
Connecting sleeve for electric tools C 35, el.	75	5.453-052.0	1 piece(s)	ID 35				Inner Ø 28 mm, outer Ø 34 mm/ 38.8 mm, el. Only NT-vacuums.	<input type="checkbox"/>
Adapter for electric power tools, screwable									
Power tool adapter, threaded, DN 35	76	5.453-016.0	1 piece(s)	ID 35				3-way plastic adapter with fitting instructions. For DN 26 to DN 36. For connecting to an industrial DN 35 suction hose. Inner Ø 28.6 mm, outer Ø 37.3/38.8 mm.	<input type="checkbox"/>
Adapter for electric power tools, screwable, ID 35	77	5.453-026.0	1 piece(s)	ID 35					<input type="checkbox"/>
Power tool adapter, threaded, DN 35	78	6.902-059.0	1 piece(s)	ID 35				Electrically conductive power tool adapter, threaded. Internal diameter: 32 mm. External diameter: 39 mm.	<input type="checkbox"/>
	79	6.902-095.0	1 piece(s)	ID 35				2-way power tool adapter, threaded. For connecting to an industrial DN 35 suction hose. Internal diameter: 28 mm. External diameter: 34 mm and 38.8 mm. Suitable for NT vacuum cleaners.	<input type="checkbox"/>
Adapter (tube -> nozzle)									
Adapter	80	5.453-019.0	1 piece(s)	ID 40				From DN 40 to DN 61: Plastic adapter (electrically non-conductive). Suitable for NT vacuum cleaners.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories.

NT 65/2 AP 1.667-297.0

KÄRCHER


		Order Number	Quantity	ID	Length	Width	Price	Description	
Reducing sleeves									
Reducer	81	5.407-108.0	1 piece(s)	ID 40				Threaded reducer - from C-40 to DN 35. Suitable for NT vacuum cleaners.	<input type="checkbox"/>
Sleeve C40 / C35	82	5.407-113.0	1 piece(s)	ID 40				Reducer (C 40 to C 35) for connecting accessories with C-35 clip connection to suction hoses with C 40 clip system.	<input type="checkbox"/>
Reducer (tube -> nozzle)									
Reducer	83	6.902-017.0	1 piece(s)	ID 40				Reducer for accessory extension. Ideal for accessories with DN 35 connecting cone in combination with accessories with DN 40 connecting cone.	<input type="checkbox"/>
Reducer from ID 35 to 32	84	6.902-072.0	1 piece(s)	ID 35				Reducer with internal connecting cone DN 32. Ideal for accessories from the industrial vacuum cleaner range in combination with industrial NT vacuum cleaners.	<input type="checkbox"/>
Set reducing / extension sleeves									
Set reducing / extension sleeves	85	2.860-117.0	1 piece(s)					ID 40/35, ID 35/32 (tube -> nozzle), plastic.	<input type="checkbox"/>
Target group specific vacuum cleaner accessory sets									
Professional cleaning kit ID 40	86	2.637-353.0		ID 40				Individual parts: Suction hose 4 m (4.440-263.0), bend, metal (6.900-276.0), suction tube 2 x 0.5 m, metal (6.900-275.0), grout nozzle (6.903-033.0), floor nozzle with rollers (6.903-051.0).	<input type="checkbox"/>
Car cleaning kit	87	2.862-166.0		ID 35				Contains: - Car cleaning nozzle ID 35 - Upholstery/crevice tool ID 35 - Suction brush ID 35 - Connecting sleeve C 35/ ID 35	<input type="checkbox"/>
Chip cleaning kit	88	2.640-760.0		ID 61				Individual parts: suction hose 4 m, oil-proof (4.440-613.0), crevice tool (6.900-222.0), rubber suction nozzle angled at 45° (6.902-106.0).	<input type="checkbox"/>
Other									
CS 40 Me	89	2.863-026.0	1 piece(s)					The highly efficient CS 40 Me cyclone preseparator for all Kärcher wet and dry vacuum cleaners is a specially designed accessory for fine dust applications on construction sites or in industry.	<input type="checkbox"/>
UBS non-conductive media									
	90	2.642-602.0	1 piece(s)					For switching off when vacuuming non-conductive fluids such as oils and greases	<input type="checkbox"/>

■ Included in delivery. □ Available accessories.