



HD 7/12-4 M Plus

The HD 7/12-4 M Plus, a powerful, robust and versatile cold water pressure washer with good accessory storage and perfect manoeuvrability for daily operation.









1 High-quality equipment

- Automatic pressure relief for protecting the components extends their service life.
- Powerful, 4-pole slow-running electric motor.

2 **Flexible operation**

- н. Designed for upright and horizontal operation.
- the ground.





3 **Outstanding mobility**

Push handle can be retracted at the push of a button, thus increasing the compactness of the machine and reducing the space requirement. Effortless storage in service vehicles.

Clever accessory storage 4

- Bracket for fixing the cup foam lance.
- Maximum stability in horizontal operation as the wheels do not touch stored directly at the machine.

TECHNICAL DATA AND EQUIPMENT.



HD 7/12-4 M Plus

Robust 4-pole low-speed AC motor

- Save energy and time: EASY!Force high-pressure guns and EASY!Lock quick-release locks.
- Automatic pressure relief and up to 20 percent higher energy efficiency

Technical data		
Order Number		1.524-936.0
EAN code		4054278504919
Current type	Ph / V / Hz	1 / 240 / 50
Flow rate	l/h	700
Operating pressure	bar / MPa	120 / 12
Max. pressure	bar / MPa	180 / 18
Max. water feed temperature	°C	60
Power rating	kW	3,1
Weight (with accessories)	kg	41,3
Dimensions (L x W x H)	mm	400 × 455 × 700
Equipment		
Trigger gun		EASY!Force
High-pressure hose	m	10 / Premium quality

119961 2011		LASTITUTC
High-pressure hose	m	10 / Premium quality
Spray lance	mm	840
Power nozzle		•
Dirt Blaster spray lance		
ANTI!Twist		-
Pressure switch control		
Servo Control		-
Quick coupling		

Included in delivery.

KÄRCHER



19 20

				1			
		Order Number	ID	Max. working pressure	Length	Price	Description
Standard with unions on both sides							
High-pressure hose, 10 m DN 8, AVS trigger gun connector	1	6.110-031.0	ID 8	315 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu- al coupling. Further data: DN 8/155°C/315 bar.
High-pressure hose, 15 m DN 8, AVS trigger gun connector	2	6.110-030.0	ID 8	315 bar	15 m		15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu- al coupling. Further data: DN 8/155°C/315 bar.
High-pressure hose, 20 m DN 8, AVS trigger gun connector	3	6.110-032.0	ID 8	315 bar	20 m		20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu- al coupling. Further data: DN 8/155°C/315 bar.
High-pressure hose, 30 m DN 8, including rotary coupling	4	6.110-014.0	ID 8	315 bar	30 m		With rotary coupling, 2 x M 22 x 1.5
High-pressure hose, 15 m DN 10, 220 bar, extension	5	6.110-042.0	ID 10	220 bar	15 m		15 m high-pressure hose M 22 x 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.
High-pressure hose, 20 m DN 10, 220 bar, extension	6	6.110-043.0	ID 10	220 bar	20 m		with union on both sides, M 22 x 1.5 with anti-kink protection. NW 10/155 $^\circ$ C/220 bar
High-pressure hose, 25 m DN 10, extension, not rotatable	7	6.110-044.0	ID 10	220 bar	25 m		
Hose assembly premium DN10 22MPa 40m	8	6.110-045.0	ID 10	220 bar	40 m		
Hose assembly premium DN12 21MPa 15m	9	6.110-059.0	ID 12	210 bar	15 m		High-pressure hose for water volumes greater than 1,800 l / h. With union on both sides. 2x M 22 x 1.5 with anti-kink
Hose assembly premium DN12 21MPa 40m	10	6.110-060.0	ID 12	210 bar	40 m		protection.
Hose assembly TR DN10 22MPa 10m	11	6.110-041.0	ID 10	220 bar	10 m		
High-pressure hose, 10 m DN 6, AVS trigger gun connector	12 13	6.110-034.0 6.110-035.0	ID 6 ID 6	250 bar 250 bar	10 m 10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manu- al coupling. Further data: DN 6/155°C/250 bar.
High-pressure hose, 10 m, DN 6, 300 bar, AVS trigger gun connec- tion	14	6.110-056.0	ID 6	300 bar	10 m		With patented AVS connection in the trigger gun (pivot- mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 6/155°C/300 bar
Longlife 400 with unions on both s	ides						
High-pressure hose packaged	15	6.110-038.0	ID 8	400 bar	10 m		Durable, 10 m long high-pressure hose (ID 8) with double steel reinforcement and EASY!Lock hand screw connection at both ends and ANTI!Twist. Approved for 400 bar pressu- re.
High-pressure hose Longlife 400, 30 m DN 8, including rotary coup- ling	16	6.110-023.0	ID 8	400 bar	30 m		With rotary coupling, 2 x M 22 x 1.5
High-pressure hose Longlife 400, 20 m, DN 8, extension	17	6.110-027.0	ID 8	400 bar	20 m		with rotary coupling, 2 x M 22 x 1.5
High-pressure hose Longlife 400, 15 m, DN 8, including rotary coup- ling	18	6.110-029.0	ID 8	400 bar	15 m		With rotary coupling, 2 x M 22 x 1.5
High-pressure hose 1.5 m, DN 8, including connectors	19	6.110-024.0	ID 8	400 bar	1,5 m		1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink pro- tection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).
Longlife 400 high-pressure hose, 1 x EASY!Lock, 1 x M22 x 1.5, DN 8, 400 bar, 1.5 m	20	6.110-069.0	ID 8	400 bar	1,5 m		High-pressure hose (ID 8) with double steel reinforcement, 1.5 m long, suitable for up to 400 bar pressure. Connectors: M 22 \times 1.5, quick and convenient EASY!Lock hand screw connection.



		Order Number	ID	Max. working pressure	Length	Price	Description	
Food industry version with unions	on bot	h sides						
High-pressure hose, 10 m ID 8, suitable for food industry, extensi- on piece	21	6.110-051.0	ID 8	250 bar	10 m		10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.	
High-pressure hose, 20 m ID 8, suitable for food industry, extensi- on piece	22	6.110-052.0	ID 8	250 bar	20 m		20 m high-pressure hose (DN 8) with swivel coupling. Non- discolouring outer layer for use in the food industry. Con- nectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.	
Longlife food industry version with	unior	s on both sides						
High pressure hose food DN 8 / 10 m	23	6.110-053.0	ID 8	400 bar	10 m		Longlife HP hose for use in the food industry. Außende- cke## animal-grease-resistant, non-colour-bleeding materi- al. With rotary coupling, 2 x M 22 x 1,5	
HIgh-pressure hose Longlife 400, 15 m, ID 6, AVS trigger gun con- nection	24	6.110-054.0	ID 8	400 bar	20 m		Longlife HP hose for use in the food industry. Außende- cke## animal-grease-resistant, non-colour-bleeding materi- al. With patented AVS connection in the pistol (pivot moun- ted)	

KARCHER



		Order Number	Flow rate		Price	Description
Trigger guns						
EASY!Force Advanced	1	4.118-005.0				Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.
Conversion kit 1 from high pressu- re hose	2	4.111-050.0				A conversion kit which enables secure connection from an M22 hose onto our innovative EASY!Force trigger gun. The kit includes the EASY!Force Trigger gun, adaptors and lance.
Conversion kit 2 from device	3	4.111-051.0				Provides all the parts required to utilise our EASY!Force technology even on our non-Easy!Force machines. Including adaptors, lance, Easy!Force trigger gun and hose.
Conversion kit 3 only EASY!Force	4	4.111-052.0				A conversion kit for the EASY!Force gun, which includes the correct adaptors to conncect to the M22 style lance and hose.
Quick connect						
Quick-fitting pipe union coupler trapezo	5	2.115-000.0				For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 x 1.5 internal thread.
Quick-fitting pipe union plug nipp- le tra	6	2.115-001.0				Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22 x 1.5 external thread.

 \blacksquare Included in delivery. $\hfill\square$ Available accessories. $\hfill\blacksquare$ Extension hose.

	7				~	5	
		Order Number	Max. working pressure	Length		Price	Description
Rotating spray lances		1		1	I		
Lance 850 mm, rotatable, ergono- mic	1	4.112-006.0	300 bar	840 mm			850 mm stainless steel lance (manual coupling) with ergono- mic handle for ease of use and protection. Rotatable 360° under pressure.
Nozzle Light	2	2.680-002.0		125 mm			LED work light for assembly on EASY!Force spray lances, providing a clear view in poor lighting conditions ensuring controlled cleaning results.
Lance 250 mm, non-rotatable	3	4.112-027.0	300 bar	250 mm			600 mm stainless steel lance (manual coupling) with ergono-
550 mm lance, non-rotatable	4	4.112-024.0	300 bar	400 mm			mic handle for ease of use and protection. Rotatable 360°
Rotatable lance, 600 mm, ergono-	5	4.112-007.0	300 bar	600 mm			under pressure.
mic 1050 mm lance, rotatable, ergono- mic	6	4.112-000.0	300 bar	1050 mm			1050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.
Lance 1550 mm, rotatable, ergo- nomic	7	4.112-018.0	300 bar	1550 mm			1550 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° [under pressure.]
Lance 2050 mm, rotatable, ergo- nomic	8	4.112-021.0	300 bar	2050 mm			2050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.
Jet pipe extension TR 1000 mm	9	4.112-048.0	300 bar	1000 mm			Spray lance extension with EASY!Lock connection. Length 1000 mm.
Double lance		1	I				1000 mm.
Double lance 960 mm	10	2.112-016.0	310 bar	960 mm			960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).
Angular spray lance		1					
WC and gutter lance	11	4.112-029.0					Stainless steel lance WC and gutter with nozzle insert. Spe- cially shaped for effective and hygienic cleaning of gutters and toilets.
Flexible spray lance		1		1	1 1		
Flexible lance 1050 mm	12	4.112-035.0	210 bar	1050 mm			1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.
Articulated joint TR 20	13	4.112-057.0	300 bar				For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer.
Telescopic spray lance							
Telescopic jet pipe	14	4.112-037.0	225 bar	5400 mm			Can be continuously extended from 1.8 to 5.4 m. For cleaning areas that are difficult to reach, such as ceilings or facades. With integrated HD trigger gun, M 22 x 1.5 connection with rotary coupling. Connection for M 18 x 1.5 nozzles.
Restraint belt for telescopic jet pipe	15	6.373-987.0					Convenient strap for relief when working with the telesco- pic spray lance (6.394-690). The burden is optimally distri- buted on the body and longer periods of use are possible.

Gutter cleaner Gutter cleaning lance 16 2.112-015.0 960 mm The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates. Undercarriage spray lance Underbody lance 17 4.112-032.0 700 mm Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.



		Order Number	Max. working pressure	Length		Price	Description
Additional handle							
Additional handle for EASY!Lock spray lances	18	4.321-380.0					Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task.
PowerControl spray lance							
PowerControl spray lance 042	19	4.112-046.0					Our PowerControl spray lance with nozzle size 042 makes possible the appropriate cleaning performance for each cleaning task. Infinitely variable and precise pressure ad- justment directly within reach.

 \blacksquare Included in delivery. $\hfill\square$ Available accessories. $\hfill A$ Extension hose.



		Order Number	Max. working pressure	Nozzle size		Price	Description
Dirt blaster, large							
Dirt blaster - without changeover function	1	4.114-042.0	300 bar	45			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.
Dirt Blaster, small							
Dirt blaster, small 045	2	4.114-021.0	180 bar	45			Up to 50% higher cleaning and area performance than its predecessor: with the new performance dirt blaster (nozzle size 045), power losses have been minimised and the spray quality maximised.
Triple nozzles							
Triple jet nozzle 045	3	4.117-036.0	300 bar	45			Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For machines with an injector, the low- pressure flat stream is useful for cleaning agent suction and application. Connection M 18 x 1.5.
Angle vario nozzle 0°-90°							
Spezial nozzle 0005	4	4.113-007.0		50			Variable angle nozzle for spray angle adjustment from 0° to 0°. For easy adjustment to all kinds of soiling and surfaces.



		Order Number	Nozzle size			Price	Description
Power nozzle spray angle 25°							· · · · · · · · · · · · · · · · · · ·
Power nozzle spray angle 25°	1	2.113-022.0	45				Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.
HP nozzle spray angle 0°							
High-pressure nozzle spray angle °0	2	2.113-033.0	45				High-pressure nozzle with powerful jet for extremely stub- born dirt.
Power nozzle spray angle 15°							·
Power nozzle spray angle 15°	3	2.113-046.0	45				Fan jet nozzle with 15° spray angle suitable for stubborn dirt.
Power nozzle spray angle 40°							· ·
Power nozzle spray angle 40°	4	2.113-053.0	45				Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces. $\hfill \Box$
■ Included in delivery. □ Av	ailable	e accessories.	▲ Extension ho	ose.			

KARCHER



		Order Number	Flow rate		Price	Description	
Cup foam lance				 			
Cup foam lance Basic 2	1	4.112-054.0	700-800 l/h			For high-pressure cleaners with a flow rate of 700-800 l/h: new, robust and very high-quality foam cup lance with outstanding foam quality while consuming half as much cleaning agent.	
Cup foam lance Advanced 042	2	2.112-018.0				Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design.	E
Tank grey only for replacement 1L	3	6.414-050.0				Additional 1-litre cleaning agent container for quick replace- ment of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	
Inno Foam Set							
Inno foam kit with detergent injec- tor	4	2.112-000.0				High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	
Easy Foam Set							
Easy Foam Set with RM injector	5	2.112-010.0				HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	t I
Nozzle kits for Inno/Easy Foam Set							
Nozzle kit 055 z. Inno/Easy Set 500 - 600 l/h	6	2.111-009.0	500-600 l/h			Optimal adaptation to different machine outputs for econo- mic use.	
Foam nozzle mounting kit							
Foam nozzle kit	7	2.112-013.0				Foaming agent kit. The foam nozzle is ideal for use in sani- tary areas and the food industry and wherever long applica- tion times are necessary.	- [





							[
		O urland March	0		Puise	De- scripti-	
		Order Number	Quantity		Price	on	
Backflow check valve							
Backflow preventer	1	2.641-374.0				To pre-	
						vent	
						deter-	
						gent	
						getting	
						into the drinking	
						water	
						cycle in	
						case of	
						inlet at	
						low-	
						pressu-	
						re hot	
						water	
						resistant	
						up to 80	
						°C - tes-	
						ted	
						accor- ding to	
						IEC	
						60335-	
						2-79	
						- integ-	
						rated	
						leakage	
						protec-	
						tion	
Geka coupling							
With hose nozzle, R 1/2"	2	6.388-461.0				with	
						hose	
						liner	
With hose nozzle, R 3/4"	3	6.388-455.0				with	
						hose	
				 		liner	
With hose nozzle, R 1"	4	6.388-465.0				with	
						hose	
With formale this D. D. / //	-	6 200 472 0				barb	-
With female thread, R 3/4"	5	6.388-473.0				with female	
						thread	
						l inread	



							De-	
		Order Number	Quantity			Price	scripti- on	
Suction filter	<u> </u>	order Nomber	Quantity			FILE		
		6 44 4 05 6 0		1	1	1	Cultable	
Water filter	6	6.414-956.0					Suitable for	
							ponds,	
							storage	
							tanks or	
							similar,	
							polyami-	
							de filter	
							casing,	
							stainless	
							steel	
							strainer,	
							800 µm	
							mesh, R	
							3/4" and	
							R 1"	
							connec-	
							tion,	
							without	
							non-	
							return valve	
weather Aller with the sharehouse bure		4 700 040 0						-
Suction filter with check valve	7	4.730-012.0					Brass suction	
							filter	
							suitable	
							for	
							ponds,	
							storage	
							tanks,	
							etc. With	
							check	
							valve.	



	Order Number	Quantity		Price	De- scripti- on	
		Quantity		Price	011	I
Fine-mesh water filter						





KARCHER

				5	$ \begin{array}{c} \begin{array}{c} \end{array}{}\\ \end{array}{}\\ \end{array}{}\\ \end{array}{}\\ \end{array}{}\\ \begin{array}{c} \end{array}{}\\ \end{array}{}\\ \end{array}{}\\ \end{array}{}\\ \end{array}{}\\ \end{array}{}\\ \end{array}{}\\ \end{array}{}$	
		Order Number		Price	Description	
Nozzle union Nozzle screws	1	4.112-011.0		1	Nozzle screws with protectors for high-pressure and power	
	1	7.112 011.0			nozzles	
HP detergent injector Stainless steel injector kit for HD 6/15C Dosing valve for stainless steel injector	2	6.645-758.0			Ideal for the HD 6/15 C high-pressure cleaner, the stainless steel injector ensures precise cleaning agent and foam dosa- ge. With suction hose and vacuum filter. Retrofittable dosing valve for stainless steel injectors. For	
Detergent injector for high and	4	4.637-032.0			easy, convenient and precise cleaning agent dosing adjust- ment via a control knob. Detergent injector for independent high and low pressure	
low pressure (without nozzles)					dosage. Maximum dosage about 15%.	
Detergent injector for high pressu- re	5	4.637-033.0			Cleaning agent dosage at high pressure 3 - 5 %	
Machine-specific nozzle kit with ord	der no	. 3.637-170	II		I	
Nozzle insert trapezoidal thread	6	4.769-005.0			For HD 500 - 700 l/h. Consists of nozzle insert + HP power	
HD-GER. Nozzle insert with order no. 3.637-0	001				nozzle + union	
Nozzle insert for Order No. 3.637- 001, high-pressure for machines up to 1100 l/h.	7	4.769-003.0			Nozzle insert for detergent injector 3.637-001 for high- pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Low pressure for units rated 1100 I/h or more	8	4.769-006.0			For low pressure with machines above 1.100 l/h	
Rotary coupling						
Rotary coupling	9	4.111-021.0			Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.	
Coupling Coupler -2xM22x1,5	10	4.111-037.0			Brass double connector for connecting and extending high- pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m.	
Connector						
Nozzle connector/screw connector	11	4.111-022.0			Nozzle connector/screw connector for connecting high- pressure nozzles and accessories to the high-pressure trig- ger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.	
Y distributor	12	4.111-024.0			Offers the option to connect two spray units to the machine	
Short spray unit	13	4.111-038.0			Installation on the high pressure outlet. For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). Not compatible with triple nozzles.	
Adapter EASY!Lock				1		
Adapter 1 M22AG-TR22AG Adapter 2 M22IG-TR22AG	14 15	4.111-029.0 4.111-030.0			Adapter 1 to connect the old hose with the new hose Adapter 2 to connect the old device with the new hose and	
					the old gun with the new hose	
Adapter 3 M22IG-TR22AG	16	4.111-031.0			Adapter 3 to connect the old gun with the new spray lance and new servo regulator	
Adapter M22 - Swivel	17	4.111-032.0			M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	
Adapter 5 TR22IG-M22AG	18	4.111-033.0			Adapter 5 to connect the new gun with the old spray lance	
■ Included in delivery □ Ava		e accessories 🔺 Extension ho			and new servo regulator with the old spray lance	



		Order Number			Price	Description	
Adapter 6 TR22IG-M22AG	19	4.111-034.0				Adapter 6 to connect the new device with the old hose and the old hose with the new gun	
Adapter 7 M18IG-TR20AG	20	4.111-035.0				Adapter 7 to connect the old spray lance with the new nozzle	
Adapter 8 TR20IG-M18AG	21	4.111-036.0				Adapter 8 to connect the new spray lance with the old nozzle	
ADAPTER for replacement TR22IG- M22AG Er	22	4.111-046.0				Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	

KARCHER




		Order Number	Max. working pressure	Nozzle size	Diame- ter	Price	Description	
Pipe cleaning hose, ID 6							I	_
Hose assembly TR pipe cleaning DN6 max.2	1	6.110-046.0	250 bar				The 10 m pipe cleaning hose is a highly flexible high pressu re hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, DN 6, 20 m, 220 bar	2	6.110-008.0	250 bar				20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle).	
Hose assembly TR pipe cleaning DN6 max.2	3	6.110-047.0	250 bar				The 30 m pipe cleaning hose is a highly flexible high pressu re hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Hose assembly TR pipe cleaning DN6 14MPa	4	6.110-048.0	140 bar				10 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	
Pipe cleaning hose	5	6.110-049.0	140 bar				20 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	
Pipe cleaning hose, DN 6, 30 m	6	6.110-050.0	140 bar				30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	
Pipe cleaning nozzle								
Dirt blaster pipe cleaning D21/040	7	4.765-001.0		40	21 mm		The forward-tilted rotating pencil jet removes the most	
Dirt blaster pipe cleaning D30/040	8	4.765-004.0		40	30 mm		stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient hand- ling.	
Pipe cleaning nozzle	9	5.763-015.0		55	16 mm		16 mm pipe cleaning nozzle with internal thread. Various je	t 🗆
	10	5.763-016.0		60	16 mm		directions for environmentally-friendly cleaning of blocked drains and pipes.	
	11	5.763-017.0		50	30 mm		30 mm pipe cleaning nozzle with internal thread. Various je directions for environmentally-friendly cleaning of blocked drains and pipes.	
Rotating pipe cleaning nozzle	12	6.415-428.0		50	16 mm		Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blo- cked drains and pipes.	

KARCHER



KARCHER

				4		5		
		Order Number	Length				Price	Description
Hose reel add-on kit					<u> </u>			
Add-on kit hose reel module	1	2.110-024.0	15 m					Hose reel attachment kit for high-pressure middle class
Automatic, self-winding hose reels								
Add-on kit hose reel plastics	2	6.392-074.0	20 m					Automatic hose reel for 20 m high-pressure hose. The con- sole is made from powder-coated steel, the drum is made from plastic.
Add-on kit hose reel	3	6.392-083.0	20 m					Automatic hose reel for 20 m high-pressure hose. The con- sole consists of stainless steel, the drum is made from plas- tic.
Hose reel, automatic, 20 m, pain- ted	4	6.392-106.0	20 m					Automatic hose reel of durable plastic. Painted steel bracket.
Hose reel, automatic, basalt grey- coated	5	6.392-105.0	20 m					Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses.
Hose reel, automatic, 20 m, stain- less steel	6	6.392-076.0	20 m					Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.
ABS hose reel stainless steel	7	6.392-122.0	20 m					High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.
Add-on kit hose reel TR 40m	8	6.392-442.0	40 m					Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compa- tible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).
Swivel holder	9	2.639-931.0						Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.
ABS wall fastening stainless steel		2.641-867.0						Swivelling wall bracket made of high-grade steel (for 2.641- 866). This makes maximum flexibility and convenience possible when working with the HP hose.



		Order Number	Flow rate	Water feed temperature	Length	Length	Price	Description		
Solar cleaning - telescopic lances										
Telescopic rod complete 14m	1	4.110-002.0		max. 60 °C				Full carbon telescopic rod for maximum rigidity with mini- mal weight. With 14 m max. reach and practical quick- release couplings for easy extension and retraction.		
Telescopic rod complete 10m CFK	2	4.110-007.0		max. 60 °C				The full carbon telescopic lance offers maximum rigidity with minimal weight. It has a reach of up to 10 m and is fitted with practical quick-release couplings – for convenient extension and retraction.		
Telescopic rod complete 10m	3	4.110-003.0		max. 60 °C				Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 10 m max. reach and practical quick-release couplings for easy extensi- on and retraction.		
iSolar TL 7 H (without hose)	4	4.110-004.0		max. 60 °C				Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 7.2 m max. reach and practical quick-release couplings for easy extensi- on and retraction.		
Hose solar	5	6.392-978.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.		
	6	6.392-977.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.		
	7	6.392-976.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.		



		Order Number	Nozzle size		Price	Description
Wet blasting attachment (without n	nozzle)					
Wet blasting attachment with flow control (without nozzles)	1	4.115-000.0				Paint, rust and scale removal made easy: Kärcher wet blas- ting attachment with flow control for adding blasting abrasi- ve to the high-pressure jet.
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0				Paint, rust and scale removal made easy: Kärcher wet blas- ting attachment with flow control for adding blasting abrasi- ve to the high-pressure jet. Without flow control.
Nozzle pack for wet blasting attach	ment					
Nozzle pack TR wet jet set 0045	3	2.112-022.0	45			Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.115-000.0 4.115-006.0.
Boron carbide nozzle						
Boron carbide nozzle, for machi- nes as of 1000 l/h	4	6.415-084.0	6 mm			In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.

 \blacksquare Included in delivery. $\hfill\square$ Available accessories. $\hfill\blacksquare$ Extension hose.



		Order Number	Flow rate		Price	Description	
Push-on washing brush						1	
Push-on wash brush, M 18 x 1.5	1	4.113-001.0				Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.	
Rotating washing brush					-		
Rotating wash brush for < 800 l/h machines, nylon bristles	2	4.113-004.0	500-800 l/h			The rotating wash brush gently removes fine dust and traf- fic film from all surfaces. Temperature resistant up to 60° C. (M 18 x 1.5, replaceable brush insert).	
Rotating wash brush for > 800 l/h machines, nylon bristles	3	4.113-002.0	800-1300 l/h			Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60°C, M 18 x 1.5 (replaceable brush insert).	
Rotating wash brush for < 800 l/h machines, natural bristles	4	4.113-003.0	500-800 l/h				
Rotating wash brush for > 800 l/h machines, natural bristles	5	4.113-005.0	800-1300 l/h				