



VehiclePro Truck Cleaner, acidic RM 804

Acid prespraying agent for commercial vehicle brush and high pressure washing facilities. Removes mineral soiling such as plaster, lime, mortar and concrete from construction site vehicles and steel structures.









Properties

- Corrosion protection on painted surfaces
- Removes mineral stains such as plaster, limescale, mortar and concrete
- Rapidly separates oil/water in the oil separator (easy to separate=asf)
- Tensides biodegradable in accordance with EEC 648/2004
- NTA free

Areas:

Building Industry: Co Car dealership and garage: Co

Haulage contractors, bus oper-

ators:

Municipal:

Commercial vehicle cleaning
Commercial vehicle cleaning

Food tankers

Vehicle cleaning

Application

- High-pressure washers
- Car wash
- Spray units

	Part number		
20	6.295-595.0		
200	6.295-598.0		







Application:

High-pressure washers

- Set the dosage and temperature on the device
- Clean object, working in overlapping sections.
- Rinse surface well with clear water.

Car wash

- Insert the product into the system.
- Adjust dosage on the device.
- Start washing programme.

Spray attachment

- Combine the product with the appropriate dosage and fresh water.
- Wet object completely with product.
- Allow to soak.
- Reaction time 1-3 minutes, depending on the degree of soiling.
- Rinse surface well with clear water.

Directions for use:

- Test on an inconspicuous part for material compatibility.
- Do not spray onto hot surfaces.
- Do not let the cleaning solution dry out.
- Avoid over-dosage.
- Store away from frost.

Further information:

■ Material Safety Data Sheet (MSDS)

Dosage and yield:

Content:	Cleaning method:	Primary mixture:	Dosage:	Contamination:	Productivity:
1000 ml	High-pressure washers		1-3 %	medium-strong	7 NKW
1000 ml	Vehicle washing bay		1-3 %	heavy	7 NKW
1000 ml	Spray units		1-3 %	medium	75 NKW

Please contact us for more information:

Kärcher UK Ltd

Kärcher House Brookhill Way Banbury Oxon OX16 3ED