




HDS 5/11 U

Entry-level, highly portable hot water pressure washer



1 Innovative upright design

- Effortless transport over landings or stairs.
- Large wheels for unpaved surfaces.

2 Fine-mesh water filter

- Efficiently protects high-pressure pump against contamination.
- Easy to remove from outside.

3 Compact design

- Space-saving storage and transport.
- Spill-proof pump and fuel tank for transport lying down.

4 Save energy and time: EASY!Force high-pressure guns and EASY!Lock quick-release locks.

- At last – work without getting tired: the EASY!Force high-pressure gun.
- EASY!Lock quick-release locks: durable and robust. And five times faster than screws.



HDS 5/11 U

- Professional entry-level model for mobile applications
- Innovative, space-saving upright design
- Flue gas temperature monitor

Technical data

Order Number		1.064-902.0
EAN code		4054278139777
Current type	Ph / V / Hz	1 / 230 - 240 / 50
Flow Rate	l/h	450
Pressure	bar / MPa	110 - 110 / 11 - 11
Temperature	°C	max. 80
Power rating	kW	2,2
Consumption fuel oil	kg/h	2,4
Fuel tank	l	6,5
Weight	kg	65,4
Dimensions (L x W x H)	mm	618 × 618 × 994
number of simultaneous users		1

Equipment

Trigger gun		EASY!Force Advanced
High-pressure hose	m	10
Spray lance	mm	840
ANTI!Twist		-
Pressure switch control		■
Servo Control		-

■ Included in delivery.

HDS 5/11 U

1.064-902.0


KÄRCHER


		Order Number	ID	Max. working pressure	Length	Price	Description	
Standard with unions on both sides								
High-pressure hose, 10 m DN 8, AVS trigger gun connector	1	6.110-031.0	8	315 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	▲
High-pressure hose, 15 m DN 8, AVS trigger gun connector	2	6.110-030.0	8	315 bar	15 m		15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	▲
High-pressure hose, 20 m DN 8, AVS trigger gun connector	3	6.110-032.0	8	315 bar	20 m		20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	▲
High-pressure hose, 30 m DN 8, including rotary coupling	4	6.110-014.0	8	315 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose, 15 m DN 10, 220 bar, extension	5	6.110-042.0	10	220 bar	15 m		15 m high-pressure hose M 22 x 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.	▲
High-pressure hose, 20 m DN 10, 220 bar, extension	6	6.110-043.0	10	220 bar	20 m		with union on both sides, M 22 x 1.5 with anti-kink protection. NW 10/155°C/220 bar	▲
High-pressure hose, 25 m DN 10, extension, not rotatable	7	6.110-044.0	10	220 bar	25 m			▲
Hose assembly premium DN10 22MPa 40m	8	6.110-045.0	10	220 bar	40 m			▲
Hose assembly premium DN12 21MPa 15m	9	6.110-059.0	12	210 bar	15 m		High-pressure hose for water volumes greater than 1,800 l/h. With union on both sides. 2x M 22 x 1.5 with anti-kink protection.	▲
Hose assembly premium DN12 21MPa 40m	10	6.110-060.0	12	210 bar	40 m			▲
Hose assembly TR DN10 22MPa 10m	11	6.110-041.0	10	220 bar	10 m			▲
High-pressure hose, 10 m DN 6, AVS trigger gun connector	12	6.110-034.0	6	250 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection.	■
	13	6.110-035.0	6	250 bar	10 m		With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 6/155°C/250 bar.	□
High-pressure hose, 10 m, DN 6, 300 bar, AVS trigger gun connection	14	6.110-056.0	6	300 bar	10 m		With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 6/155°C/300 bar	□
Longlife 400 with unions on both sides								
High-pressure hose Longlife 400, 30 m DN 8, including rotary coupling	15	6.110-023.0	8	400 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose Longlife 400, 20 m, DN 8, extension	16	6.110-027.0	8	400 bar	20 m		with rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose Longlife 400, 15 m, DN 8, including rotary coupling	17	6.110-029.0	8	400 bar	15 m		With rotary coupling, 2 x M 22 x 1.5	▲
Longlife 400 high-pressure hose, 1 x EASY!Lock, 1 x M22 x 1.5, DN 8, 400 bar, 1.5 m	18	6.110-069.0	8	400 bar	1.5 m		High-pressure hose (ID 8) with double steel reinforcement, 1.5 m long, suitable for up to 400 bar pressure. Connectors: M 22 x 1.5, quick and convenient EASY!Lock hand screw connection.	□
Food industry version with unions on both sides								
High-pressure hose, 10 m ID 8, suitable for food industry, extension piece	19	6.110-051.0	8	250 bar	10 m		10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.	▲
High-pressure hose, 20 m ID 8, suitable for food industry, extension piece	20	6.110-052.0	8	250 bar	20 m		20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.	▲

■ Included in delivery. □ Available accessories. ▲ Extension hose.


HDS 5/11 U

1.064-902.0

KÄRCHER


		Order Number	Flow Rate					Price	Description
Trigger guns									
EASY!Force Advanced	1	4.118-005.0							Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero. ■
Conversion kit 1 from high pressure hose	2	4.111-050.0							A conversion kit which enables secure connection from an M22 hose onto our innovative EASY!Force trigger gun. The kit includes the EASY!Force Trigger gun, adaptors and lance. □
Conversion kit 2 from device	3	4.111-051.0							Provides all the parts required to utilise our EASY!Force technology even on our non-Easy!Force machines. Including adaptors, lance, Easy!Force trigger gun and hose. □
Conversion kit 3 only EASY!Force	4	4.111-052.0							A conversion kit for the EASY!Force gun, which includes the correct adaptors to connect to the M22 style lance and hose. □
Quick connect									
Quick-fitting pipe union coupler trapezo	5	2.115-000.0							For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 x 1.5 internal thread. □
Quick-fitting pipe union plug nipple	6	2.115-001.0							Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22 x 1.5 external thread. □

■ Included in delivery. □ Available accessories. ▲ Extension hose.



		Order Number	Max. working pressure	Length				Price	Description
Rotating spray lances									
Lance 850 mm, rotatable, ergonomic	1	4.112-006.0	300 bar	840 mm					850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. <input checked="" type="checkbox"/>
Nozzle Light	2	2.680-002.0		125 mm					LED work light for assembly on EASY!Force spray lances, providing a clear view in poor lighting conditions ensuring controlled cleaning results. <input type="checkbox"/>
Lance 250 mm, non-rotatable	3	4.112-027.0	300 bar	250 mm					600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. <input type="checkbox"/>
400 mm rotatable lance	4	4.112-024.0	300 bar	400 mm					400 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. <input type="checkbox"/>
Rotatable lance, 600 mm, ergonomic	5	4.112-007.0	300 bar	600 mm					600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. <input type="checkbox"/>
1050 mm lance, rotatable, ergonomic	6	4.112-000.0	300 bar	1050 mm					1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. <input type="checkbox"/>
Lance 1550 mm, rotatable, ergonomic	7	4.112-018.0	300 bar	1550 mm					1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. <input type="checkbox"/>
Lance 2050 mm, rotatable, ergonomic	8	4.112-021.0	300 bar	2050 mm					2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. <input type="checkbox"/>
Jet pipe extension TR 1000 mm	9	4.112-048.0	300 bar	1000 mm					Spray lance extension with EASY!Lock connection. Length 1000 mm. <input type="checkbox"/>
Double lance									
Double lance 960 mm	10	2.112-016.0	310 bar	960 mm					960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning). <input type="checkbox"/>
Angular spray lance									
WC and gutter lance	11	4.112-029.0							Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets. <input type="checkbox"/>
Flexible spray lance									
Flexible lance 1050 mm	12	4.112-035.0	210 bar	1050 mm					1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters. <input type="checkbox"/>
Articulated joint TR 20	13	4.112-057.0	300 bar						For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer. <input type="checkbox"/>
Telescopic spray lance									
Telescopic jet pipe	14	4.112-037.0	225 bar	5400 mm					Can be continuously extended from 1.8 to 5.4 m. For cleaning areas that are difficult to reach, such as ceilings or facades. With integrated HD trigger gun, M 22 x 1.5 connection with rotary coupling. Connection for M 18 x 1.5 nozzles. <input type="checkbox"/>
Restraint belt for telescopic jet pipe	15	6.373-987.0							Convenient strap for relief when working with the telescopic spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible. <input type="checkbox"/>
Gutter cleaner									
Gutter cleaning lance	16	2.112-015.0		960 mm					The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates. <input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 5/11 U

1.064-902.0




		Order Number	Max. working pressure	Length			Price	Description	
Undercarriage spray lance									
Underbody lance	17	4.112-032.0		700 mm				Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	<input type="checkbox"/>
Additional handle									
Additional handle for EASY!Lock spray lances	18	4.321-380.0						Comfortable in every situation - the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task.	<input type="checkbox"/>
PowerControl spray lance									
PowerControl spray lance 034	19	4.112-045.0						The cleaning performance can be adapted to the respective task in an instant. The low pressure mode for the application of the cleaning agent and the adjustment of the jet level round off the product.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 5/11 U

1.064-902.0



		Order Number	Max. working pressure	Nozzle size			Price	Description	
Triple nozzles									
Triple Nozzle	1	4.117-027.0	300 bar	32				Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For machines with an injector, the low-pressure flat stream is useful for cleaning agent suction and application. Connection M 18 x 1.5.	■
Dirt blaster, large									
Dirt Blaster Nozzle	2	4.114-040.0	300 bar	35				The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	□

■ Included in delivery.
 □ Available accessories.
 ▲ Extension hose.

HDS 5/11 U 1.064-902.0



1-5

		Order Number	Nozzle size				Price	Description	
HP nozzle spray angle 0°									
Power Nozzle	1	2.113-001.0	40					High-pressure nozzle with powerful jet for extremely stubborn dirt.	<input type="checkbox"/>
Power nozzle spray angle 15°									
Power Nozzle	2	2.113-002.0	33					Flat jet nozzle for stubborn dirt.	<input type="checkbox"/>
Power nozzle spray angle 25°									
Power Nozzle	3	2.113-063.0	33					Fan jet nozzle for large-area coverage and stubborn dirt and stains.	<input type="checkbox"/>
Chemical nozzle	4	2.113-020.0	250					Brass power nozzle for low-pressure operation and cleaning agent suction.	<input type="checkbox"/>
Power nozzle spray angle 40°									
Power Nozzle	5	2.113-003.0	40					Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 5/11 U

1.064-902.0


KÄRCHER


		Order Number						Price	Description	
Nozzle union										
Nozzle screws	1	4.112-011.0							Nozzle screws with protectors for high-pressure and power nozzles	<input type="checkbox"/>
HP detergent injector										
Detergent injector for high and low pressure (without nozzles)	2	4.637-032.0							Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	<input type="checkbox"/>
Detergent injector for high pressure	3	4.637-033.0							Cleaning agent dosage at high pressure 3 - 5 %	<input type="checkbox"/>
Machine-specific nozzle kit with order no. 3.637-170										
Nozzle insert trapezoidal thread HDS-GER	4	4.769-009.0							For HDS 500 - 700 l/h. Consists of nozzle insert + HP power nozzle + union	<input type="checkbox"/>
Nozzle insert with order no. 3.637-001										
Nozzle insert for Order No. 3.637-001, high-pressure for machines up to 1100 l/h.	5	4.769-003.0							Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	<input type="checkbox"/>
Low pressure for units rated up to 1100 l/h	6	4.769-001.0							For low pressure with machines up to 1.100 l/h	<input type="checkbox"/>
Rotary coupling										
Rotary coupling	7	4.111-021.0							Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.	<input type="checkbox"/>
Coupling										
Coupler -2xM22x1,5	8	4.111-037.0							Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m.	<input type="checkbox"/>
Connector										
Nozzle connector/screw connector	9	4.111-022.0							Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.	<input type="checkbox"/>
Y distributor	10	4.111-024.0							Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.	<input type="checkbox"/>
Short spray unit	11	4.111-038.0							For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). Not compatible with triple nozzles.	<input type="checkbox"/>
Adapter EASY!Lock										
Adapter 1 M22AG-TR22AG	12	4.111-029.0							Adapter 1 to connect the old hose with the new hose	<input type="checkbox"/>
Adapter 2 M22IG-TR22AG	13	4.111-030.0							Adapter 2 to connect the old device with the new hose and the old gun with the new hose	<input type="checkbox"/>
Adapter 3 M22IG-TR22AG	14	4.111-031.0							Adapter 3 to connect the old gun with the new spray lance and new servo regulator	<input type="checkbox"/>
Adapter M22 - Swivel	15	4.111-032.0							M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	<input type="checkbox"/>
Adapter 5 TR22IG-M22AG	16	4.111-033.0							Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	<input type="checkbox"/>
Adapter 6 TR22IG-M22AG	17	4.111-034.0							Adapter 6 to connect the new device with the old hose and the old hose with the new gun	<input type="checkbox"/>
Adapter 7 M18IG-TR20AG	18	4.111-035.0							Adapter 7 to connect the old spray lance with the new nozzle	<input type="checkbox"/>
Adapter 8 TR20IG-M18AG	19	4.111-036.0							Adapter 8 to connect the new spray lance with the old nozzle	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 5/11 U

1.064-902.0




		Order Number					Price	Description	
ADAPTER for replacement TR22IG-M22AG Er	20	4.111-046.0						Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	<input type="checkbox"/>
Flue pipe									
Flue gas adapter	21	4.656-149.0						Flue gas adapter with draught damper for flue pipe connection (adapter for HDS burners for connection to a stack system).	<input type="checkbox"/>
	22	4.656-080.0							<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.



		Order Number	Max. working pressure	Nozzle size	Diameter		Price	Description	
Pipe cleaning hose, ID 6									
Hose assembly TR pipe cleaning DN6 max.2	1	6.110-046.0	250 bar					The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	<input type="checkbox"/>
Pipe cleaning hose, DN 6, 20 m, 220 bar	2	6.110-008.0	250 bar					20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle).	<input type="checkbox"/>
Hose assembly TR pipe cleaning DN6 max.2	3	6.110-047.0	250 bar					The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	<input type="checkbox"/>
Pipe cleaning nozzle									
Dirt blaster pipe cleaning D21/040	4	4.765-001.0		40	21 mm			The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling.	<input type="checkbox"/>
Dirt blaster pipe cleaning D30/040	5	4.765-004.0		40	30 mm				<input type="checkbox"/>
Nozzle pipe cleaning size 120	6	5.763-089.0		120	24 mm			Pipe cleaning nozzle with 24 mm diameter. With 8 nozzles tilted back at a 30° angle.	<input type="checkbox"/>
Pipe cleaning nozzle	7	5.763-015.0		55	16 mm			16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	<input type="checkbox"/>
	8	5.763-016.0		60	16 mm				<input type="checkbox"/>
	9	5.763-017.0		50	30 mm			30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	<input type="checkbox"/>
Rotating pipe cleaning nozzle	10	6.415-428.0		50	16 mm			Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.



		Order Number	Flow Rate	Nozzle size	Diameter	Price	Description	
Hard Surface Cleaner FRV 30								
Add-on kit hose attachment	1	2.642-528.0					Suction cup for fixing the suction hose to smooth surfaces.	<input type="checkbox"/>
Add-on kit dirt trap	2	2.642-532.0					Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.	<input type="checkbox"/>
Hard surface cleaner FRV 30 ME								
FRV 30 ME surface cleaner	3	2.111-013.0			300 mm		Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	<input type="checkbox"/>
Machine-specific nozzle kit for FR								
Nozzle kit for surface cleaners (type-specific) 450 - 500 l/h	4	2.640-482.0	450 - 500 l/h				Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (450 to 500 l/h).	<input type="checkbox"/>
Machine-specific nozzle kits for FRV								
Nozzle kit 035 - for FRV	5	2.642-430.0		35			Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30.	<input type="checkbox"/>
Hard surface cleaner FRV 30 Me								
Extension hose FRV 30 Me and FRV 50 Me	6	4.441-040.0					5 m extension hose for FRV 30 Me. Includes connecting adapter.	<input type="checkbox"/>
FRV 30 Me Surface Cleaner	7	2.111-012.0					Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.	<input type="checkbox"/>

■ Included in delivery. ☐ Available accessories. ▲ Extension hose.

HDS 5/11 U


1.064-902.0

KÄRCHER



		Order Number	Flow Rate				Price	Description	
Cup foam lance									
Cup foam lance Basic 1	1	4.112-053.0	350 - 600 l/h					For high-pressure cleaners with a flow rate of 350-600 l/h: new, robust and very high-quality foam cup lance with outstanding foam quality while consuming half as much cleaning agent.	<input type="checkbox"/>
Bottle cleaning agents 1L	2	5.071-414.0							<input type="checkbox"/>
Cup foam lance Advanced 042	3	2.112-018.0						Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design.	<input type="checkbox"/>
Tank grey only for replacement 1L	4	6.414-050.0						Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	<input type="checkbox"/>
Foam nozzle mounting kit									
Foam nozzle kit	5	2.112-013.0						Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.




		Order Number	Length					Price	Description	
Automatic, self-winding hose reels										
Wall-mounted hose reel	1	2.639-257.0	15 m						Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	<input type="checkbox"/>
Add-on kit hose reel plastics	2	6.392-074.0	20 m						Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	<input type="checkbox"/>
Add-on kit hose reel	3	6.392-083.0	20 m						Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	<input type="checkbox"/>
Hose reel, automatic, 20 m, painted	4	6.392-106.0	20 m						Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses.	<input type="checkbox"/>
Hose reel, automatic, basalt grey-coated	5	6.392-105.0	20 m						Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	<input type="checkbox"/>
Hose reel, automatic, 20 m, stainless steel	6	6.392-076.0	20 m						High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrosion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.	<input type="checkbox"/>
ABS hose reel stainless steel	7	6.392-122.0	20 m						Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).	<input type="checkbox"/>
Add-on kit hose reel TR 40m	8	6.392-442.0	40 m						Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	<input type="checkbox"/>
Swivel holder	9	2.639-931.0							Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	<input type="checkbox"/>
ABS wall fastening stainless steel	10	2.641-867.0								

■ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 5/11 U

1.064-902.0



		Order Number	Flow Rate	Water feed temperature	Length	Length	Price	Description	
Teleskopstangen									
Ball valve	1	4.580-097.0		max. 40 °C					<input type="checkbox"/>
Telescope lance glass fibre 7 m	2	4.762-609.0		max. 60 °C					<input type="checkbox"/>
Telescope lance hybrid 7 m	3	4.762-610.0		max. 60 °C					<input type="checkbox"/>
Telescope lance hybrid 10 m	4	4.762-611.0		max. 60 °C					<input type="checkbox"/>
Telescope lance carbon 10 m	5	4.762-612.0		max. 60 °C					<input type="checkbox"/>
Telescope lance carbon 14 m	6	4.762-613.0		max. 60 °C					<input type="checkbox"/>
Pistol	7	4.775-154.0		max. 60 °C					<input type="checkbox"/>

■ Included in delivery.
 □ Available accessories.
 ▲ Extension hose.

HDS 5/11 U

1.064-902.0

KÄRCHER



		Order Number	Nozzle size				Price	Description	
Wet blasting attachment (without nozzle)									
Wet blasting attachment with flow control (without nozzles)	1	4.115-000.0						Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	<input type="checkbox"/>
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0						Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	<input type="checkbox"/>
Nozzle pack for wet blasting attachment									
Nozzle pack TR wet jet set 0035	3	2.112-021.0	35					Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.115-000.0 4.115-006.0.	<input type="checkbox"/>
Boron carbide nozzle									
Boron carbide nozzle, for machines as of 1000 l/h	4	6.415-084.0	6 mm					In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 5/11 U

1.064-902.0

KÄRCHER



		Order Number			Price	Description	
Geka coupling							
With hose nozzle, R 1/2"	1	6.388-461.0				with hose liner	<input type="checkbox"/>
With hose nozzle, R 3/4"	2	6.388-455.0				with hose liner	<input type="checkbox"/>
With hose nozzle, R 1"	3	6.388-465.0				with hose barb	<input type="checkbox"/>
Suction filter							
Water filter	4	6.414-956.0				Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 µm mesh, R 3/4" and R 1" connection, without non-return valve	<input type="checkbox"/>
Suction filter with check valve	5	4.730-012.0				Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	<input type="checkbox"/>

■ Included in delivery. ☐ Available accessories. ▲ Extension hose.

HDS 5/11 U

1.064-902.0



		Order Number			Price	Description	
Fine-mesh water filter							
Fine-mesh water filter with adapter	6	4.730-102.0				Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	<input type="checkbox"/>
Water supply hose							
Water supply hose	7	4.440-038.0				NW 13 R1" / R 3/4", up to 30 °C	<input type="checkbox"/>
	8	4.440-207.0				NW 19 R1" / R 3/4", up to 85 °C, for pick-up	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

HDS 5/11 U
1.064-902.0



		Order Number			Price	De- scripti- on	
Backflow check valve							
Backflow preventer	9	2.641-374.0				To pre- vent deter- gent getting into the drinking water cycle in case of inlet at low- pressu- re. - hot water resistant up to 80 °C - tes- ted accor- ding to IEC 60335- 2-79 - integ- rated leakage protec- tion	<input type="checkbox"/>

■ Included in delivery. ☐ Available accessories. ▲ Extension hose.

HDS 5/11 U 1.064-902.0

KÄRCHER



		Order Number	Flow Rate				Price	Description	
Push-on washing brush									
Push-on washing brush	1	4.762-497.0						With clamp for mounting directly to units' double or triple nozzle. Fits on new double and triple nozzles.	<input type="checkbox"/>
Push-on wash brush, M 18 x 1.5	2	4.113-001.0						Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.	<input type="checkbox"/>
Rotating washing brush									
Rotating wash brush for < 800 l/h machines, nylon bristles	3	4.113-004.0	500 - 800 l/h					The rotating wash brush gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 60°C. (M 18 x 1.5, replaceable brush insert).	<input type="checkbox"/>
Rotating wash brush for < 800 l/h machines, natural bristles	4	4.113-003.0	500 - 800 l/h					Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60°C, M 18 x 1.5 (replaceable brush insert).	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.