CLEANWEL HIGH PRESSURE

CLEANING EQUIPMENT



CLEANER

Also available

- Performances ranging from 1500 psi 100 bar to 3000 psi 200 bar in 110v, 240v. 415v
- This is built as cold water wall mounted machine and comes with its own wall mounting kit
- It's also available with the facility to supply it with hot water up to 85 degrees centigrade on selected models
- Fitted as standard with 24 volt control, anti leak detection and auto time delayed shut down at zero pressure which has proven to reduce maintance costs by 75%
- To prolong the life of the chassis it is constructed of steel which is zintec coated with a polyester finish with a stainless steel cover. Also available in all Stainless Steel
- Long life, slow revving, industrial 1400 RPM electric motor coupled to a brass headed Interpump pump
- Supplied with 9m high pressure hose, on/off gun, lance & nozzle
- Designed and manufactured by Cleanwell to comply with CE Legislation
- 1 Year warranty subject to conditions of sale

British Manufacturer

let Cleanwell handle the pressure

WALL MOUNT COLD WATER PRESSURE CLEANERS

PERFORMANCE SPECIFICATIONS							
Operating Pressure		Flow Rate	Voltogo	Motor			
PSI	Bar	Litres Per Minute	Voltage	Motor			
1500	100	12	110v	3.0 HP			
1500	100	12	240v	3.4 HP			
1500	100	14	240v	3.4 HP			
2200	150	14	415v	5.5 HP			
2200	150	21	415v	7.5 HP			
2500	175	18	415v	7.5 HP			
3000	200	15	415v	7.5 HP			

SPECIFICATIONS

Pump	3 Piston Plunger Interpump	Maximum Inlet Temp.	50°C
Motor	Slow Revving Industrial Motor 2 Motor Bearing	Chemical System	Low Pressure Chemical Injection
Auto Time Stop	Adjustable – Factory Set 2 minutes	Electric Cable	240v 30ft/9m 415v 20ft/6m
Low Voltage Controls	24 volts 240v	Weight	70kg
Dimensions	Height 385mm	Width 750mm	Depth 830mm

OPTIONS

5 ltr Water break tank	Frost Protection	Remote Control
Key Isolator	Water Softener	Start/Stop from Gun
Sprung Loaded Booms (In stainless steel)	High Pressure Chemical Injection	Coin Mec Box (For token operation)