

MC 6P

Performance, ergonomics and long life




The MC 6P industrial-class cold-water pressure washers combine unbeatable lifetime, top-grade cleaning performance, and optimal ergonomics to comprise a highly competitive range of heavy-duty pressure washers for use in industry, agriculture, shipping, transport, and food production.

The MC 6P-120/1950 XT in particular combines a high water performance with a low power consumption.

- Industrial 4 ceramic-piston pump with 80°C inlet temp
- Highly durable 30 mm steel frame
- Optimal storage and transport with foldable handle and easy lifting points
- High mobility thanks to large rear wheels and front castor with parking brake
- Maintenance-friendly service concept – easy access to pump
- Ergo accessory concept
- Flow-controlled control system
- Low-pump oil safety switch
- Water-flow regulation on pump



3 Year Guarantee



TECHNICAL SPECIFICATIONS

| Description | MC 6P-120/1950 FA | MC 6P-120/1950 FAXT |
|---|-------------------|---------------------|
| Item no. | 107146773 | 107146774 |
| Pump pressure (bar/MPa) | 120 / 12 | 120 / 12 |
| Cleaning impact (kg/force) | 8.2 | 8.2 |
| Water flow Qmax / Qiec (l/h) | 1850 / 1950 | 1850 / 1950 |
| Max. inlet temperature (°C) | 80 | 80 |
| Pump (RPM) | 1450 | 1450 |
| Dimensions L x W x H (mm) | 930 x 570 x 1020 | 930 x 570 x 1020 |
| Weight (kg) | 89 | 96 |
| Power consumption (kW) | 7.5 | 7.5 |
| Voltage / phase / frequency / current (V~/Hz/A) | 400 / 3 / 50 / 16 | 400 / 3 / 50 / 16 |
| El cable (m) | 8 | 8 |
| Suction height dry (m) | 1 | 1 |
| Nozzle size | 1500 | 1500 |
| Features: | | |
| Pistons / number of pistons | Ceramic / 4 | Ceramic / 4 |
| Automatic start / stop | • | • |
| Low pump oil safety | • | • |
| Water flow regulation | • | • |
| Additional hose and rotary jet lance | | • |
| Detergent tank (l) | 1 x 2.5 | 1 x 2,5 |
| Hose reel | | • |
| Foam canon incl. 1 l tank | | • |
| Standard equipment: | | |
| HP hose (DN10) | 610766 (10 m) | 1402064 (15 m) |
| High flow spray gun | 106404530 | 106404530 |
| Ergo coupling | 101119496 | 101119496 |
| Water inlet coupling | 61369 | 61369 |
| Hose reel | | 106403143 |
| Tornado Plus lance without HP nozzle | 106403010 | 106403010 |
| TurboHammer Plus lance with HP nozzle | | 106408269 |
| Tornado Plus nozzle | 101119762 | 101119762 |

Nilfisk Ltd.

Nilfisk House · Bowerbank Way · Gilwilly Industrial Estate · Penrith · Cumbria · CA11 9BQ
 Tel.: 01768 868995 (UK) · 01 2943838 (IE)
 Email: mail.uk@nilfisk.com (UK) · info.ie@nilfisk.com (IE)
 www.nilfisk.co.uk · www.nilfisk.ie

