



Telescopic lance TL 7 F

Telescopic lance TL 7 F with up to 7 m reach made from robust and lightweight glass fibre. With practical quick-release fasteners for simple retraction and extension.




1 Multifunctional use

- For window, facade and solar panel cleaning with osmosis water.
- For high-pressure cleaning or low-pressure cleaning with wash brushes.



2 Maximum ergonomics

- Quick-release fasteners for fast and simple loosening of the lance clamping.
- Rotatable base ensures simple and ergonomic working.



3 Very user-friendly

- Tool-free adjustment of the clamping force at the quick-release fasteners.
- With clamping hooks to guide water hose outside the lance.



4 Maximum safety

- Haptic and visual pull-out stopper avoids unintentional disassembly.
- Non-electroconductive base-lance element.



Telescopic lance TL 7 F

Technical data

Order no.		4.762-609.0
EAN code		4054278716206
Length of the telescopic handle	m	2-7
Inlet temperature	°C	max. 60
Material		Fibreglass
Elements		5
Connection thread		M 18
Weight incl. packaging	kg	5.1

Equipment

Tool less clamp force adjustment	■
Tool-less clamp force adjustment	■
Hose hook	■
Pull out stopper	■

TELESCOPIC LANCE TL 7 F

4.762-609.0



		Order no.	Flow rate	Inlet temperature	Length	Length	Price	Description	
Teleskopstangen									
TL low pressure adapter	1	4.580-097.0		max. 40 °C				TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes.	<input type="checkbox"/>
TL high pressure adapter	2	4.775-154.0		max. 60 °C				TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals.	<input type="checkbox"/>

Available accessories.

TELESCOPIC LANCE TL 7 F

4.762-609.0



		Order no.	Flow rate	Inlet temperature	Length	Length	Price	Description	
Schläuche									
iSolar HP hose 7	1	6.392-978.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	<input type="checkbox"/>
Water hose 25 m	2	6.392-578.0		max. 60 °C				Water hose (25 m) for water connection to brushes mounted on telescopic lances for window, façade and solar power installation cleaning.	<input type="checkbox"/>
Water hose 50 m	3	6.392-579.0		max. 60 °C				50-metre transparent water hose as supply line for the brushes mounted on telescopic lances for window, façade and solar power installation cleaning.	<input type="checkbox"/>

Available accessories.

TELESCOPIC LANCE TL 7 F

4.762-609.0



		Order no.					Price	Description	
Machine accessories									
Shoulder strap universal	1	2.042-016.0						Ergonomic and convenient universal shoulder strap. For long, fatigue-free work with leaf blowers, lawn trimmers or multi-tools from Kärcher.	<input type="checkbox"/>

Available accessories.